

CAPTAIN

EU MODEL 263 (25 HP)



CAPTAIN
AGRI MACHINERY



THE **ROAR** GETS **LOUDER**
FROM THE **LAND** OF **LIONS**



Powered by
MITSUBISHI
DIESEL ENGINE

8G
THE EIGHTH
GENERATION

Note : Products undergo continuous upgradations.

www.captainagri.com

EU-ENGLISH

CAPTAIN

EU MODEL 263 - STAGE V

Powered by
 **MITSUBISHI DIESEL ENGINE**

8G
 THE EIGHTH
 GENERATION



Italian Designed Lion Face



Hydrostatic Power Steering



Engine : Stage V Mitsubishi 3 Cylinder



Gear levers on the Side



Front Opening Bonnet



Ergonomic Seating & Footboard Area



850 kg Hyd. Lifting Capacity



2 PTO Speeds



Differential Lock



Multi Disc Oil Immersed Brakes



Smart ADDC (2 Lever) Hydraulics

Narrow Track Option Separately Available in this Model



	SPECIFICATIONS	CAPTAIN 263 4WD Agriculture	CAPTAIN 263 4WD Turf	CAPTAIN 263 4WD Industrial / Flotation	CAPTAIN 263 4WD Agricultural Wide Plus	CAPTAIN 263 4WD Agrimax Turf RT 333 Garden	CAPTAIN 263 4WD Wider F-Agri	CAPTAIN 263 4WD Industrial (Regular)	CAPTAIN 263 4WD Basic - Agri	CAPTAIN 263 4WD Agricultural Wide
Engine	Engine Horse Power (kW)	25 (18.2)								
	Engine Type	Mitsubishi Stage-V S3L2								
	No. of Cylinder	3								
	Capacity (CC)	1319								
	Rated Speed (RPM)	2500								
	Cooling System	Liquid Cooled								
	Bore / Stroke (mm)	78/92								
Max Torque (Nm) @ RPM	76.3 (Nm) @ 2000 RPM									
Tyres	Front	180/85D12	23 x 8.5 - 12	23 x 8.5 - 12	180/85D12	240/60R12	23 x 8.5 - 12	23 x 8.5 - 12	5.00 x 12	6.5/80-12
	Rear	8.30 x 20	33 x 15.5 - 16.5	33 x 15.5 - 16.5	280/70R20	320/65R18	280/70R18	12 x 16.5	8.00 x 18	280/70R18
Transmission	Type	Sliding Mesh Transmission : Side Shift Gear Levers								
	Gears	9 Forward, 3 Reverse								
	Max. Speed (km / hr.)	20.83	19.15	19.83	20.76	19.90	19.55	19.73	18.96	19.55
	PTO RPM	540 & 540 E								
	Steering	Hydrostatic Power Steering								
Hyd.	Brake Type	Multi Disc Oil Immersed								
	Hydraulic System	Auto Draft Sensing & Depth Control (2 Levers)								
	Lift Capacity (kgs.)	850 (at Lower Link Point)								
	No. of Pumps	2 (One for Hydrostatic Steering & Other for Hydraulic System)								
Dimensions #	Auxiliary Hydraulics	1 DA Auxiliary Hydraulics with 2 QRCs								
	Size LxWxH (mm)	2700* x 1080 x 2100	2700* x 1490 x 2050	2700* x 1490 x 2050	2700* x 1167 x 2095	2700* x 1206 x 2065	2700* x 1220 x 2060	2700* x 1252 x 2060	2700* x 1050 x 2060	2700* x 1200 x 2060
	Wheel Base (mm)	1490	1490	1490	1490	1490	1490	1490	1490	1490
	Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	887	845 to 988	944	743 to 988	845 to 988
	Weight (kg)	950	992	1020	981	981	956	994	929	952

*Dimensions are with Standard Lower Links, it may vary with longer linkages.

+/- 5% Tolerance variations

Note : Products undergo continuous upgradations. Hence, above mentioned specifications are subject to change without prior notice.